

ANGLE BROOMS

BA72 | BA84



JOHN DEERE



Angle Brooms

BA72 | BA84



Specifications

- Angle brooms feature an 812-mm (32 in.)-diameter brush with 50/50 poly-wire brush segments.
- Standard storage stands prevent bristles from flattening, helping ensure that the brush stays round when not in use.
- Standard hydraulic angling with parallel swing arms keeps the broom centered throughout the entire swing arc.
- Maximum angle 30 deg. left or right.
- Heavy-duty, high-torque drive motor is coupled to the brush core through a 25.4-mm (1 in.) splined shaft.
- Bristle replacement is neat and easy. Drive motor separates from the brush core without disconnecting any hydraulic hoses, virtually eliminating the possibility of hydraulic-fluid spillage.
- Standard rubber deflector directs dust down and away from the operator.
- Optional roof-mounted water tank kit is available for jobs that require prolonged dust control.
- Operation is easy. Just set the initial brush position, lower the vehicle broom onto the stops, and curl the broom backward so the bristles skim the surface to be swept.
- Like all Worksite Pro™ attachments, these angle brooms are optimized to work with John Deere G- and E-Series Skid Steers and Compact Track Loaders (CTLs), and are compatible with most competitive models. See your local Deere skid steer dealer for details.

| | BA72 | BA84 |
|------------------------------|---|---|
| Brush Diameter | 812 mm (32 in.) | 812 mm (32 in.) |
| Core Diameter | 254 mm (10 in.) | 254 mm (10 in.) |
| Sweeping Width | | |
| Straight | 1828 mm (72 in.) | 2133 mm (84 in.) |
| Fully Angled 30 deg. | 1587 mm (62.5 in.) | 1854 mm (73 in.) |
| Overall Width | | |
| Straight | 2209 mm (87 in.) | 2514 mm (99 in.) |
| Fully Angled 30 deg. | 2108 mm (83 in.) | 2374 mm (93.5 in.) |
| Operating Weight | 454 kg (1,000 lb.) | 545 kg (1,200 lb.) |
| Hydraulic Flow | | |
| Minimum | 38 lpm (10 gpm) | 38 lpm (10 gpm) |
| Maximum | 114 lpm (30 gpm) | 114 lpm (30 gpm) |
| Number of Wafers | 44 | 50 |
| Angle Control | Electric over hydraulic | Electric over hydraulic |
| Vehicle Compatibility | 318G/E, 320E, 324E, 328E, and 332E Skid Steers; and 317G, 323E, 329E, and 333E CTLs | 318G/E, 320E, 324E, 328E, and 332E Skid Steers; and 317G, 323E, 329E, and 333E CTLs |

WORKSITE PRO™

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

