

MULCHING HEAD

MH60C (Two Speed)



JOHN DEERE



Mulching Head

MH60C (Two Speed)



Specifications

- Remove up to 203-mm (8 in.) trees and 305-mm (12 in.) stumps. Shred underbrush and woody materials into beneficial mulch in just minutes.
- Severe-duty design utilizes oversize 64-mm (2.5 in.) sealed rotor bearings and double carbide-tipped teeth for long-term durability. Heavy-duty push bar is useful for toppling trees or brush, and helps protect the carrier.
- Two-speed hydraulic system efficiently utilizes available horsepower. When preset pressure level is attained, the motor automatically shifts to a higher displacement, increasing torque for reduced stalling and faster rotor speed recovery. Prominently positioned gauge lets an operator easily monitor hydraulic operating pressure for additional efficiency.
- Hydraulic brake stops the rotor in less than 10 seconds, eliminating the “freewheeling” common with other designs.
- Optional hydraulic cooler is available for operation in high-ambient-temperature conditions.
- With a 1524-mm (60 in.) opening and 30 teeth, high-capacity rotor takes big bites out of trees and stumps. Rotor is balanced to deliver superior large-material knockdown and shredding performance. Also works well below soil level for chewing out stumps.
- Smooth rotor reduces material drag and horsepower requirements. Internal counter-combs help shatter incoming material, creating a finer mulch.
- Optional hydraulically operated mulching plate retains material within the shroud for maximum material shredding.
- Like all Worksite Pro™ attachments, this mulching head is optimized to work with John Deere skid steers and compact track loaders. See your local John Deere skid steer dealer for details.

	MH60C
Overall Width	1880 mm (74 in.)
Maximum Cutting Width	1524 mm (60 in.)
Height	1452 mm (57 in.)
Length	1550 mm (61 in.)
Weight	1118 kg (2465 lb.)
Recommended Flow	125–144 lpm (33–38 gpm)
Maximum Hydraulic Pressure	4,000 psi
Flow (standard or high)	High
Number of Cutting Tools	30 double-carbide tipped
Vehicle Compatibility	326D/E, 328D/E, and 332D/E Skid Steers; 329D/E and 333D/E Compact Track Loaders

WORKSITE PRO™

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

