



JOHN DEERE



STEEL TRACKS

10-IN. | 12-IN. | 14-IN.



WORKSITE PRO

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

- Worksite Pro™ steel tracks allow 200 and 300 Series Skid Steers to operate in soft, muddy, loose conditions, while also improving traction over hard ground and gravel.
- Design reduces ground pressure, while adding counter-balance weight.
- Use of tracks protects tires from damaging terrain, and allows long tread life.
- Heavy-duty bushings (1.25 in.) and drilled (not cored) holes increase strength.
- Sloped link casting helps eject material that could interfere with movement.
- Tracks are easy to clean and adjust due to open outer side plate.

Skid steer compatibility	240, 250, 317, 320 with 10-in. tires	250, 320 with 12-in. tires	260, 270, 325, 328 with 12-in. tires	260, 270, 280, 328, 332 with 14-in. tires
Track pitch	10 in. (254 mm)	10 in. (254 mm)	10 in. (254 mm)	10 in. (254 mm)
Total number of pads	36	36	40	42
Track weight	731 lb. (332 kg)	792 lb. (360 kg)	920 lb. (418 kg)	1,066 lb. (484 kg)
Weight per pad	21.5 lb. (9.8 kg)	22 lb. (9.9 kg)	23 lb. (10.4 kg)	27.4 lb. (12.4 kg)
Pin diameter	1.25 in. (31.7 mm)	1.25 in. (31.7 mm)	1.25 in. (31.7 mm)	1.25 in. (31.7 mm)
Pin wear length	0.75 in. (19 mm)	0.75 in. (19 mm)	0.75 in. (19 mm)	0.75 in. (19 mm)
Pin wear surface area	1.17 sq. in. (30 mm ²)	1.17 sq. in. (30 mm ²)	1.17 sq. in. (30 mm ²)	1.17 sq. in. (30 mm ²)
Pin heat-treated	Yes, 55-60 RC	Yes, 55-60 RC	Yes, 55-60 RC	Yes, 55-60 RC
Pin installation	Bolted	Bolted	Bolted	Bolted
Pin field replaceable	Yes	Yes	Yes	Yes
Link thickness	0.75 in. (19 mm)	0.75 in. (19 mm)	0.75 in. (19 mm)	0.75 in. (19 mm)
Crossbar dimension (two bars)	1 x 1.25 in. (25 x 32 mm)	1 x 1.25 in. (25 x 32 mm)	1 x 1.25 in. (25 x 32 mm)	1 x 1.25 in. (25 x 32 mm)
Crossbar height	1.3 in. (33 mm)	1.3 in. (33 mm)	1.3 in. (33 mm)	1.3 in. (33 mm)
Crossbar wear area (per pad)	21.5 sq. in. (546 mm ²)	22.4 sq. in. (569 mm ²)	25.5 sq. in. (647 mm ²)	27.2 sq. in. (691 mm ²)
Crossbar heat-treated	Yes	Yes	Yes	Yes
Traction bead	2 per pad	2 per pad	2 per pad	2 per pad
Tire guide area (per pad)	60 sq. in. (1523 mm ²)	60 sq. in. (1523 mm ²)	60 sq. in. (1523 mm ²)	60 sq. in. (1523 mm ²)
Binder provided	Yes	Yes	Yes	Yes
Length adjustment	Yes	Yes	Yes	Yes
Flotation area of tires	396 sq. in. (2554.8 cm ²)	504 sq. in. (3251.6 cm ²)	504 sq. in. (3251.6 cm ²)	605 sq. in. (3903.2 cm ²)
Flotation area with tracks	832 sq. in. (5367.7 cm ²)	1,102 sq. in. (7109.6 cm ²)	1,102 sq. in. (7109.6 cm ²)	1,280 sq. in. (8258 cm ²)

WORKSITE PRO™

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

